


[DIMENSIONS OF CONNECTOR]

[PRECAUTIONS FOR HANDLING]

◆Connector insertion and extraction
 a. Connector shall be extracted vertically by specialised extraction JIG.
 Part No. : U.FL-LP-N-2 (CL Code: CL331-0494-5)
 Never hold the cable when extracting the cable because it damages the connector.
 b. Insert the connector as perpendicularly to the mating surface as possible by aligning the mating axes of both connectors. Do not excessively slant the connectors when inserting.

◆Allowable loads on the cable after the connectors are mated.
 The figures below show the maximum allowable loads on the cable. Do not apply loads exceeding these values to the cable.



RoHS COMPLIANT

| | | | | | | | |
|--------------------------------|-------------|-----------------|-----------|--------------------------|----------------------------|---------|------|
| 1 | U.FL-LP-088 | CL331-0454-0 | 2 | FWS5032(GRAY) | KURABE INDUSTRIAL CO.,LTD. | | |
| NO. | PART NO. | CODE NO. | NO. | PART NO. | MANUFACTURER | | |
| UNITS mm | | SCALE FREE | COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE |
| HIROSE ELECTRIC CO.,LTD. | APPROVED | : TS. NOBE | 11.08.25 | DRAWING NO. | EDC4-304298-07 | | |
| | CHECKED | : NK. NINOMIYA | 11.08.24 | PART NO. | U.FL-LP-088KIT-A-(400) | | |
| | DESIGNED | : MS. MATSUMOTO | 11.08.23 | CODE NO. | CL321-3247-5-07 | | |
| | DRAWN | : MS. MATSUMOTO | 11.08.23 | | | | |