

PART NUMBER: 334CKH050M

RADIAL LEAD GENERAL PURPOSE

Parts are RoHS compliant



FEATURES

105°C, low cost, small size

APPLICATIONS

Filtering, Bypass, coupling

ELECTRICAL SPECIFICATIONS

Capacitance: 0.33 μ F

Dissipation Factor: 0.1 Max at 120 Hz

Temperature Range: -55°C to +105°C

ESR: 502.38 Ohms Max at 20°C and 120 Hz

Impedance: N/A

Tolerance: -20 % , +20 %

WVDC: 50 Volts DC

SVDC: 63 Volts DC

Ripple Current: 10 mA at 120 Hz and 105°C

Impedance Ratios: -25°C/20°C - 2
-40°C/20°C - 3

Leakage Current: .03CV or 4 μ A, whichever is greater 4 μ A after 1 Minute

.01CV or 3 μ A, whichever is greater
3 μ A after 2 Minutes

Load Life: 2000 hours at 105°C with 100 % of rated voltage and with 100 % of rated ripple current

Max Capacitance Change: $\leq$ 20% of initially measured value

Dissipation Factor Change: $\leq$ 200% of maximum specified value

Leakage Current: $\leq$ 100% of maximum specified value

Ripple Current Multipliers

Frequency Multipliers:

50 Hz	120 Hz	400 Hz	1 kHz	10 kHz	100 kHz
0.8	1	1	1.15	1.25	1.25

Temperature Multipliers:

45°C	60°C	70°C	65°C	75°C	85°C	105°C	125°C
1.75	1.75	1.4	1.75	1.4	1.4	1	0

PHYSICAL DIMENSIONS

Diameter (D): 5 mm +/- 0.5 mm

Length (L): 11 mm, +/- 1.5 mm


Lead Spacing (S): 2 mm, +/- 0.5 mm

Lead Wire Diameter (d): 0.5 mm, +/- 0.05 mm

Lead Length (LL): 15 mm, +/- MIN mm

Lead Finish: Matte Tin

Coating: Brown PVC sleeving



3757 W. Touhy Ave. Lincolnwood, IL 60712 (847)-675-1760 FAX (847)-673-2850
Illinois Capacitor (HK) Ltd., Tel: 85227930931, Fax: 85227930731, www.ilcap.com.hk
© 2012 Illinois Capacitor