




FUSE CLIPS & HOLDERS

9/32 FUSE CLIP



CAT. NO. 3565


.020 Brass, Nickel Plate Current Rating: 15 Amps



13/32 PC FUSE CLIP



.028 Brass, Tin Plate Current Rating: 30 Amps



Mounting Detail .089 DIA HOLE \(\)

CAT. NO. 3566

CUSTOM FUSE CLIPS & HOLDERS

Keystone is fully integrated to meet your total design & production needs.


Manufacturing custom designs & modifications of standard items is our specialty.

Quotations on special fuse clips & holders furnished promptly upon receipt of sample, sketch, print or CAD drawings.

PC 5mm FUSE HOLDERS

SLIM LINE & (OPTIONAL) COVER





Mounting Detail 052 DIA. (2) PLS

Optional cover with window protects and insulates fuse


CAT. NO. 4628 - Holder CAT. NO. 4628C - Cover only (with window)

SPECIFICATIONS

Base & Cover: Nylon, UL94V-0 Contacts: Brass, Tin Plate Rated: 5 Amp @ 250V

LOW PROFILE & (OPTIONAL) COVER






Low profile, space saving design Optional cover protects and insulates fuse

CAT. NO. 4527 - Holder CAT. NO. 4527C - Cover only SPECIFICATIONS

Base & Cover: Nylon, UL94V-0 Contacts: Brass, Tin Plate Rated: 5 Amp @ 250V

PC SNAP-IN FUSE HOLDER





- Low profile, space saving design
- Snap-in design for wave soldering
- Optional cover protects and insulates fuse

CAT. NO. 3527 - Holder CAT. NO. 3527C - Vinyl cover only

-.900 .078 DIA. (2) PLS

Mounting Detail


SPECIFICATIONS

Base: .062 G-10, UL Rated 94V-0 Clips: Brass, Tin Plate Rated: 6.3 Amps @ 250V


3AG

5mm & 3AG FUSE COVERS





5_mm



CAT. NO. 3527C

CAT. NO. 4245C