

# 824-WIPES

# ISOPROPYL ALCOHOL WIPE Safety Data Sheet

**Section 1: Identification** 

**Product Identifier and Other Means of Identification** 

Product Name: Isopropyl Alcohol Wipe

Other Means of Identification: 824-Wipes

**Related Part #** 824-WX25, 824-WX50, 824-WX500

## **Recommended Use and Restriction on Use**

Use: Cleaning wipes

**Uses Advised Against:** Industrial Use Only. Not for use on monitor screens or glass with anti-glare coatings

## **Details of Manufacturer or Importer**

Manufacturer MG Chemicals 1210 Corporate Drive Burlington, Ontario L7L 5R6 CANADA

 Image: matrix with the system
 +1-800-340-0772

 Fax
 +1-800-340-0773

 E-MAIL
 support@mgchemicals.com

 WEB
 www.mgchemicals.com

MG Chemicals (Head Office) 9347-193 Street Surrey, British Columbia V4N 4E7 CANADA

<b>æ</b>	+1-905-331-1396
FAX	+1-905-331-2682
E-MAIL	info@mgchemicals.com

E-маіц (Competent Person): <u>sds@mgchemicals.com</u>

## **Emergency Phone Number**

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents) USA or CANADA—Call Verisk 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)

**For emergencies involving the transport of dangerous goods**; 24/7 service CANADA—Call CANUTEC collect at **+1-613-996-6666** or **\*666** on cellular phones

Page 1 of 14



**824-WIPES** 

## Section 2: Hazard(s) Identification

#### **Classification of Hazardous Chemical**

#### **GHS Categories**

Criteria		Category	Signal Word	Pictograms
Flammable Liquid		2	Danger	Flame
Eye irritation		2A	Warning	Exclamation
Specific Target Organ Toxicity	Single Exposure	3	Warning	Exclamation
	Single Exposure	3	5	

*Note:* The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity). Severity categories rankings do not allow comparisons between classes.

#### **Label Elements**

Signal Word	DANGER
Pictograms	Hazard Statements
	H225: Highly flammable liquid and vapor
· · ·	H319: Causes serious eye irritation
	H336: May cause drowsiness or dizziness
Prevention	Precautionary Statements
P210	Keep away from heat, hot surfaces, sparks, flames, and other ignition sources. No Smoking.
P261	Avoid breathing vapors or mist.
P271	Use only outdoors or in well-ventilated area.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves and eye protection.

Section continued on the next page

Page 2 of 14



# **824-WIPES**

Continued	
Continueu	

Response	Precautionary Statements	
P370 + P378	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.	
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P337 + P313	If eye irritation persists: Get medical advice or attention.	
P304 + P340, P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE or doctor if you feel unwell.	
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.	
Storage	Precautionary Statements	
P403 + P235	Store in well-ventilated place. Keep cool.	
Disposal	Precautionary Statements	
P501	Dispose of contents in accordance to local, regional, national, and international regulations.	

## Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None

## Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
67-63-0	propan-2-ol <sup>a)</sup>	99.7%

a) Commonly known as isopropyl alcohol (IPA)



# **ISOPROPYL ALCOHOL WIPE**

**824-WIPES** 

Section 4: First-Aid Measures			
Exposure Condition	GHS Code: Precautionary Statement		
IF IN EYES	P305 + P351 + P338, P337 + P313		
Immediate Symptoms	redness, irritation, tearing, pain		
Response	Rinse cautiously with water for 20 minutes or more. Remove contact lenses, if present and easy to do. Continue rinsing.		
	If eye irritation persists: Get medical advice or attention.		
IF INHALED	P304 + P340, P312		
Immediate Symptoms	cough, dizziness, drowsiness, headaches, weakness		
Response	Remove person to fresh air and keep comfortable for breathing.		
	Call a POISON CENTRE or doctor if you feel unwell.		
IF ON SKIN (or hair)	P303 + P361 + P353		
Immediate Symptoms	Low toxicity: redness, dry skin, mild irritation		
Response	Take off immediately all contaminated clothing. Rinse skin with water.		
IF SWALLOWED	P301 + P330, P331		
Immediate Symptoms	Low toxicity: nausea, dizziness, weakness, headaches		
Response	Rinse mouth. Do NOT induce vomiting.		
Section 5: Fire-Fighting	Measures		

Response	In case of fire: Use dry chemical, carbon dioxide, water fog, or chemical foam to extinguish. Use water spray to cool containers.
Specific Hazards	Vapors may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion.
<b>Combustion Products</b>	Produces carbon oxides (CO, CO <sub>2</sub> )
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.



# 824-WIPES

## Section 6: Accidental Release Measures

Personal Protection	See personal protection equipment in Section 8.
Precautions for Response	Remove or keep away all sources of ignition or extreme heat. Avoid breathing vapors.
Environmental Precautions	Not applicable
Containment	Not applicable
Cleaning	Collect wipes in a sealable, solvent-resistant container.
Disposal Methods	Dispose of spill waste according to Section 13.

Section 7: Handling and Storage		
Prevention	Keep out of reach of children.	
	Keep away from heat, hot surfaces, sparks, flames, and other ignition sources. No Smoking.	
	Avoid breathing vapors or mist. Use only outdoors or in a well- ventilated area.	
Handling	Wear protective gloves and eye protection.	
	Wash hands thoroughly after handling.	
Storage	Store in a well-ventilated area. Keep cool.	

Page 5 of 14



# **ISOPROPYL ALCOHOL WIPE**

# **824-WIPES**

# Section 8: Exposure Controls/Personal Protection

#### Substances with Occupational Exposure Limit Values

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
propan-2-ol	ACGIH	200 ppm	400 ppm
	U.S.A. OSHA PEL	400 ppm	Not established
	Canada AB	200 ppm	400 ppm
	Canada BC	200 ppm	400 ppm
	Canada ON	200 ppm	400 ppm
	Canada QC	400 ppm	500 ppm

*Note:* The ACGIH1, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS database<sup>2</sup> and from suppliers' SDS were also consulted. Short term exposure limits (STEL) are usually for 15 min and long term permissible exposure limits (PEL) for 8 h.

#### **Engineering Controls**

Keep airborne concentrations below exposure limits.
quipment
Wear appropriate protective eyeglasses or chemical safety goggles.
<b>RECOMMENDATION:</b> Use safety glasses with lateral protection (side shields).
For likely contacts, use of protective butyl rubber, nitrile, neoprene, polyethylene gloves or other chemically resistant gloves.
For incidental contacts, use disposable nitrile or neoprene gloves, or other chemically resistant gloves.
Do NOT use latex rubber, polyvinyl alcohol (PVA) or PVC gloves.
Section continued on the next page



Respiratory

Protection

#### ISO 9001:2015 Quality Management System SAI Global File #004008 Burlington, Ontario, Canada

# **ISOPROPYL ALCOHOL WIPE**

**824-WIPES** 

For over-exposures up to 10 x OEL of vapors or mist, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

**RECOMMENDATION:** Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

## **General Hygiene Considerations**

Wash hands thoroughly with water and soap after handling.

# **Section 9: Physical and Chemical Properties**

Physical State	Liquid, in solid mixture	Lower Flammability Limit	2%
Appearance	Colorless	Upper Flammability Limit	12%
Odor	Alcohol like	Vapor Pressure @20 °C	4.2 kPa [32 mmHg]
Odor Threshold	0.44 ppm	Vapor Density	2.1 (Air =1)
рН	Not available	Relative Density @25 °C	0.785
Freezing/Melting	-88 °C	Solubility in	Fully miscible
Point	[-126 °F]	Water	
Initial Boiling Point	≥81.8 °C	Partition Coefficient	Not
	[≥179 °F]	n-octanol/water	available
Flash Point <sup>a)</sup>	12 °C	Auto-ignition	425 °C
	[54 °F]	Temperature	[797 °F]
Evaporation	1.5	Decomposition	Not
Rate	(ButAc = 1)	Temperature	available
Flammability	Highly	Viscosity	2.4 mPa·s
	flammable	@20 °C	[3.1 mm²/s]

a) Tag closed cup value



824-WIPES

# Section 10: Stability and Reactivity

Reactivity	At elevated temperatures, may react with aluminum and generate hydrogen gas.
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Avoid ignition sources, excessive heat, and incompatible substances.
Incompatibilities	Strong oxidizing agents, strong acids, strong bases, halogenated compounds, aluminum at temperatures $\geq$ 49 °C [ $\geq$ 120 °F]
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

# Section 11: Toxicological Information

## Summary of Effects and Symptoms by Routes of Exposure

Eyes	Causes eye redness, serious eye irritation, tearing, or pain.
Skin	May cause redness or a mild irritation.
Inhalation	May cause drowsiness or dizziness. Excessive exposure may cause narcotic effects, weakness, and headaches.
Ingestion	See inhalation symptoms.
Chronic	Prolonged or repeated exposure may defat skin and cause skin dryness and cracking, and local redness and discomfort.

## Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50	LD50	LC50
	oral	dermal	inhalation
propan-2-ol	5 840 mg/kg	12 800 mg/kg	16 000 ppm
	Rat	Rabbit	8 h Rat

*Note:* Toxicity data from the RTECS<sup>2</sup> and ECHA databases were consulted. The data from supplier SDS were also consulted.

Section continued on the next page

Page 8 of 14



# 824-WIPES

Other	<b>Toxicological Effect</b>	S
-------	-----------------------------	---

Skin corrosion/irritation	Based on available data, the classification criteria are not met. Causes mild skin irritation based on Draize tests on rabbits.
Serious eye damage/irritation	Causes severe eye irritation: propan-2-ol is a severe irritant based on Draize tests on rabbits.
Sensitization (allergic reactions)	Based on available data, the classification criteria are not met.
Carcinogenicity (risk of cancer)	Propan-2-ol is not classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.
<b>Mutagenicity</b> (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
<b>Reproductive</b> <b>Toxicity</b> (risk to sex functions)	Based on available data, the classification criteria are not met.
<b>Teratogenicity</b> (risk of fetus malformation)	Based on available data, the classification criteria are not met.
STOT-single exposure	Propan-2-ol can affect the central nervous system by inhalation causing drowsiness or dizziness.
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.

## **Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<u>http://echa.europa.eu</u>), and other reliable sources.

Based on available data, propan-2-ol does not meet the environmental toxicant classification with LC50 and EC50 >100 mg/L.

• Propan-2-ol has a minimal LC50 96 h of 9 640 mg/L for Pimephales promelas (fathead minnow); an EC50 24 h of 5 102 mg/L Daphnia magna (water flea); and an EC50 72 h of 2 000 mg/L Desmodesmus subspicatus (green algae).

## **Acute Ecotoxicity**

Available toxicity data does not meet classification thresholds

Section continued on the next page

Page **9** of **14** 



**824-WIPES** 

## **Chronic Ecotoxicity**

Available toxicity data does not meet classification thresholds

#### **Biodegradability**

The constituents are volatile.

## Other Effects

Regulated Volatile Organic Content (VOC) = 100% (785 g/L)

#### **Section 13: Disposal Information**

Dispose of contents in accordance with all local, regional, national, and international regulations.

## **Section 14: Transport Information**

#### Ground

**Refer to TDG** (Canadian Transportation of Dangerous Goods regulations) and **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.** 

824-WX25, 824-WX50, 824-WX500	
NOT REGULATED as per	FOR REFERENCE ONLY
US.DOT. Special Provision 47	UN number: UN3175
TDG Special Provision 56	Shipping Name: SOLIDS CONTAINING
	FLAMMABLE LIQUIDS, N.O.S. (isopropanol)
NOTE: Net Fill of 2 ml per	Class: 4.1
packet	Packing Group: II
	Marine Pollutant: No

Section continued on the next page

Page **10** of **14** 



# 824-WIPES

#### Air

#### Refer to ICAO-IATA regulations.

824-WX25, 824-WX50, 824-WX500	
NOT REGULATED as per	FOR REFERENCE ONLY
Special Provisions A46	UN number: UN3175
	Shipping Name: SOLIDS CONTAINING FLAMMABLE
On air waybill, write: "Not restricted	LIQUIDS, N.O.S. (isopropanol)
as per special provision A46".	<b>Class:</b> 4.1
	Packing Group: II
NOTE: <b>Net Fill</b> of 2 ml per packet	Marine Pollutant: No

**Special Provision A46**: Mixtures of solids which are not subject to these Regulations and flammable liquids may be transported under this entry without first applying the classification criteria of Division 4.1, providing there is no free liquid visible at the time the substance is packaged and the packaging must pass a leakproofness test at the Packing Group II level. Small inner packagings consisting of sealed packets or articles containing less than 10 mL of a Packing Group II or III flammable liquid absorbed into a solid material are not subject to these Regulations provided there is no free liquid in the packet or article.

## Sea

## Refer to IMDG regulations.

824-WX25, 824-WX50, 824-WX500	
NOT REGULATED as per	FOR REFERENCE ONLY
Special Provisions 216	UN number: UN3175
	Shipping Name: SOLIDS CONTAINING
NOTE: Net Fill of 2 ml per packet	FLAMMABLE LIQUIDS, N.O.S. (isopropanol)
	Class: 4.1
	Packing Group: II
	Marine Pollutant: No

**Special Provision 216**: Mixtures of solids which are not subject to the provisions of this Code and flammable liquids may be transported under this entry without first applying the classification criteria of class 4.1, provided there is no free liquid visible at the time the substance is loaded or at the time of the packaging or cargo transport unit is closed. Each cargo transport unit shall be leakproof when used as a bulk container. Sealed packets and articles containing less than 10 mL of a packing group II or III flammable liquid absorbed into a solid material are not subject to the provisions of this Code provided there is no free liquid in the packet or article.

# *Note:* Shipper must be appropriately <u>trained and certified</u> before involvement with the transport of dangerous goods.



824-WIPES

## Section 15: Regulatory Information

## Canada

## Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL.

## Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

#### USA

## **Other Classifications**

#### **HMIS® RATING**

HEALTH:	*	2
FLAMMABILITY:		3
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend: 0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

**CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45

This product contains up to 99.7% propan-2-ol (CAS # 67-63-0) which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

Section continued on the next page

Page 12 of 14



# **824-WIPES**

**California Proposition 65** (Chemicals known to cause cancer or reproductive toxicity, USA).

This product does not contain any of the listed substances.

#### Europe

RoHS (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

## Section 16: Other Information

**SDS Prepared by** MG Chemicals Regulatory Department

Date of Revision28 February 2020

Supersedes 29 September 2016

Reason for Changes: Update to the emergency phone numbers.

#### Reference

1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).

2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Section continued on the next page

Page **13** of **14** 



# **ISOPROPYL ALCOHOL WIPE**

# **824-WIPES**

#### Abbreviations

- ACGIH American Conference of Governmental Industrial Hygienists (USA)
- ECHA European Chemicals Agency
- EU European Union
- EC50 Half maximal effective concentration
- EL50 Half maximal effective loading
- IARC International Agency for Research on Cancer
- NOELR No observable effect loading ratio
- NTP National Toxicology Program
- GHS Globally Harmonized System of Classification of Labeling of Chemicals
- LC50 Lethal Concentration 50%
- LCLo Lowest published lethal concentration
- LD50 Lethal Dose 50%
- OEL Occupational Exposure Limit
- PEL Permissible Exposure Limit
- SDS Safety Data Sheet
- STEL Short-Term Exposure Limit
- TCLo Lowest published toxic concentration
- TWA Time Weighted Average
- VOC Volatile Organic Content

**Technical Queries** Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at <u>www.mgchemicals.com</u>.

Email: <a href="mailto:support@mgchemicals.com">support@mgchemicals.com</a>

Mailing Addresses Manufacturing & Support

Head Office

1210 Corporate Drive Burlington, Ontario, Canada L7L 5R6 9347–193rd Street Surrey, British Columbia, Canada V4N 4E7

**Disclaimer** This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.

Page **14** of **14**