



enabling technologies

[10 Gig Ethernet](#)
[Data Centers](#)
[Fiber System Deployment](#)
[Grounding System for Data Centers](#)
[Industrial Ethernet](#)
[Managing the Physical Layer](#)
[Network Security](#)
[Power Over Ethernet](#)

product information

[Products](#)
[Bill of Material](#)
[My Catalog](#)
[Part Search](#)
[Cross Reference](#)
[FAQ's](#)
[Download / Request Literature](#)
[Downloads](#)

resources to help you

[Evaluate Technologies](#)
[Design a Solution](#)
[How to Buy](#)
[Evaluate, Design & Install Products](#)
[Download Panduit Logo](#)
[White Papers](#)
[RoHS Compliance](#)

value added services

[Strategic Alliance Program](#)
[Consultants](#)
[Distributors](#)
[Installers](#)
[System Integrators](#)
[Warranties](#)

Product Information: Products

[USA](#) | [Heat Shrink & Abrasion Protection](#) | [Heat Shrink](#) | [General Purpose, Flexible Polyolefin for Dry Locations](#) |
HSTT Heat Shrink 4 ft (1.2M) Pieces



evaluate

[FAQs](#)

design a solution

install & maintain

- Shrink ratio of 2:1 insulates a wide range of diameters and irregular shapes
- Cross-linked, UV resistant material improves flame retardancy, chemical, and temperature resistance

For clear, add "C" to end of part number package suffix (Example HSTT05-48-QC). Contact customer service for additional color information.

^ Meets Mil Spec AMS-DTL-23053/5 Class 1.

Part Number	HSTT100-48-5
Product Family	HSTT Heat Shrink 4 ft (1.2M) Pieces
RoHS Compliant	Compliant
Part Description	Thin Wall Polyolefin Heat Shrink
Material	Flame retardant polyolefin cross-linked except clear [^]
Color	Black [‡]
CSA Certified	Yes
Military Specification	AMS-DTL-23053/5 Class 1
UL Recognized	E122770
Length (Ft.)	4
Flammability Rating	Flame Retardant
Max. Recovered I.D. (In.)	.500
Max. Recovered I.D. (mm)	12.7
Min. Expanded I.D. (In.)	1.00
Min. Expanded I.D. (mm)	25.4
Nominal Diameter / Size	1
Nominal Recovered Wall Thickness (In.)	.035
Nominal Recovered Wall Thickness (mm)	.9
Shrink Ratio	2:1
Std. Pkg. UOM	PK
Temperature Range	-67°F to 275°F (-55°C to 135°C)
UOM	PC

Std. Pkg. Qty.	5
Min. Order Qty	5
BOM Qty. (# of Pkgs.)	

Add to My Catalog

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' features.

[legal information](#) | [privacy policy](#) | [site map](#)

Copyright © 1995-2005, PANDUIT CORP. All rights reserved.