



**Network and Electrical Solutions**  
UNIFIED PHYSICAL INFRASTRUCTURE<sup>SM</sup>

Worldwide

[Home](#) [Industries](#) [Solutions](#) [Products](#) [Partners](#) [Support](#) [About Us](#) [Careers](#)

## Search Results

### Evaluate

- FAQ's

### How to Buy

- Bill of Material

- Favorite Products List

- Locate Distributor

## Home > Products Overview > Search Results >

Current refinements (click  to remove) [Search Tips](#)  Within Results

Text Search: 'HSTT50-C'

Your search criteria matched only one product, shown below

### HSTT50-C



Flexible Polyolefin DRY-SHRINK™ Heat Shrink Tubing

- General Purpose heat shrink tubing for dry locations
- Applications include insulating, protecting, harnessing and identifying wires.
- Material Type: Crosslinked Polyolefin
- Shrink Ratio: 2:1
- Temperature Range: -67°F to 275°F (-55°C to 135°C)
- Flammability Rating: Flame retardant EXCEPT clear
- Voltage: 600 V
- UL Recognized, CSA Certified
- Mil Spec: AMS-DTL-23053/5 Class 1 (Colors) Class 2 (Clear)

- Part Number
- RoHS Compliancy Status
- Part Description
- Material
- Color
- CSA Certified
- Military Specification

HSTT50-C  
Compliant  
Thin Wall Polyolefin Heat Shrink  
Polyolefin cross-linked  
Black  
Yes  
AMS-DTL-23053/5 Class 1

▪ UL Recognized	E122770
▪ Flammability Rating	Flame Retardant
▪ Length Per Reel (ft.)	100
▪ Length Per Reel (m)	30.5
▪ Max. Recovered I.D. (In.)	.250
▪ Max. Recovered I.D. (mm)	6.4
▪ Min. Expanded I.D. (In.)	.500
▪ Min. Expanded I.D. (mm)	12.7
▪ Nominal Diameter / Size	.500
▪ Nominal Recovered Wall Thickness (In.)	.025
▪ Nominal Recovered Wall Thickness (mm)	.6
▪ Pricing Description	Heat Shrink Thin, .50"(12.7mm) Dia, Black
▪ Shrink Ratio	2:1
▪ Temperature Range	-67°F to 275°F (-55°C to 135°C)
▪ Min. Order UOM	RL
▪ Min. Order Qty.	1
▪ BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
▪ Add to Favorite Product List	<input type="checkbox"/>

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

[Home](#) | [Industries](#) | [Solutions](#) | [Products](#) | [Partners](#) | [Support](#) | [Contact Us](#) | [Site Map](#) | [Careers](#)

Copyright © 1995-2008, PANDUIT CORP. All rights reserved. | [Legal Information](#) | [Privacy Policy](#)