

Search Results

Evaluate

- FAQ's

How to Buy

- Bill of Material

- Favorite Products List

- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips  Within Results

 Text Search: 'KP-HSTT2'


Your search criteria matched only one product, shown below

KP-HSTT2



DRY-SHRINK™ Heat Shrink Plastic Kit Boxes

- Provides organized storage for a wide variety of parts in one convenient location
- Informative label eliminates guess work:
 - Specifies correct heat shrink usage based on wire range and connector size
 - Provides reorder part number information
- Once top is closed loose pieces remain in their 6 compartments
- Shrink Ratio: 2:1
- Flammability Rating: Flame Retardant EXCEPT Clear
- Voltage: 600V
- UL Recognized, CSA Certified
- Mil Spec: AMSDTL-23053/5 Class 1 (Colors) Class 2 (Clear)

Part Number	KP-HSTT2
RoHS Compliancy Status	Compliant
Part Description	Heat shrink kit box- plastic case, various sizes, various colors.
Material	Polyolefin cross-linked
Color	Includes: Red Yellow Green Blue White Clear and Black
CSA Certified	Yes
Military Specification	AMS-DTL-23053/5 Class 1 (Colors) Class 2 (Clear)
Contents	35 ea. (5 ea color) 3/32", 1/8" 21 ea. (3 ea color) 3/16", 1/4" 7 ea. (1 ea color) 3/8", 1/2"
Number of Pieces by Diameter	35 Each HSTT09 3/32" (2.4mm) I.D. 7 Colors 25 Each HSTT12 1/8" (3.2mm) I.D. 7 Colors 21 Each HSTT19 3/16" (4.8mm) I.D. 7 Colors 21 Each HSTT25 1/4" (6.4mm) I.D. 7 Colors 7 Each HSTT38 3/8" (9.5mm) I.D. 7 Col
Pricing Description	Heat Shrink Thin Kit, .19".50"(4.8mm- .5mm), Multicolor
Temperature Range	-67°F to 275°F (-55°C to 135°C)
Min. Order UOM	KT
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.