

CABLE-D-15SUB/F/OE/0,25/S/2,0M


Order No.: 2926111

The figure shows the 25-pos. version

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2926111>

Shielded cable with a 15-pos. D-SUB female connector and one open end. The individual wires are labeled 1 to 15 and fitted with ferrules. The braided shield is routed to a separate cable end. Cable length: 2 m.

Commercial data

GTIN (EAN)	 4 046356 547970
sales group	I682
Pack	1 pcs.
Customs tariff	85444290
Catalog page information	Page 294 (IF-2011)

Product notesWEEE/RoHS-compliant since:
02/09/2010

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data**General**

Nominal voltage U_N	125 V AC/DC
Max. current carrying capacity per path	2 A
Max. conductor resistance	$\leq 0.09 \Omega/m$

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Number of positions	15
Number of positions, control side	15
Number of connectors, control side	0
Plug connector, module side	D-SUB socket (IEC 60807-2/DIN 41652)
Number of positions, module side	15
Number of connectors, modul side	1
Fixed cable length	2 m
Single wire, cross section	0.25 mm ²
AWG	24
External diameter	9 mm
Shielding	yes
	Tinned copper-braided shield, approx. 85% covering
Insertion/withdrawal cycles	> 200

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;