

DC Connector, Plug, 5.5x3.3 mm, 2-pole, angled, with cable



Description

- pre-assembled cable
- Low Voltage DC Plug and Socket
- DC Plug: 2-pole, angled

Weblinks


[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [RoHS](#), [CHINA-RoHS](#), [Mating Connectors](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#)

Technical Data

Diameter	5.5 mm / 3.3 mm / 1.0 mm
Number of Poles	2-pole
Ratings DC	2A / 13.5VDC
Dielectric Strength	500VDC
Insulation Resistance	> 100 MΩ @ 500VDC

Allowable Operation Temp.	-20°C to 70°C
Terminal	Cable
Cord Length	1.8 m
Cable Length	2 x 0.3 mm ²
Style	angled
Lifetime	5000 Insertions

Dimensions



Variants

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
DC Plug/Socket	5.5	2-pole	Cable	4840.5221

Packaging unit 200 Pcs

Mating Outlets/Connectors

Category / Description



[DC Plug/Socket Overview complete](#)

DC Connector, Socket, 5.9 mm, 1.05 mm, 2-pole, solder terminal

4840.2220

DC Connector, Socket, 6.0 mm, 2-pole, solder terminals for PCB

4840.2221

[DC Plug/Socket further types to 4840 DC-Stecker, verschiedene](#)