



# Zero Charge Anti-Stat Coating

## 1726

Techspray's ESD-safe products can help maintain work areas within the ANSI/ESDS20.20 standards set by the ESD Association ([www.esda.com](http://www.esda.com)).

In a static-free environment, the work area, tools and personnel form a circuit (see diagram to right). Electrostatic Discharge (ESD) occurs when the charges of two surfaces with a large electronic potential (difference) equalize instantaneously. The resulting discharge or spark can cause catastrophic or latent damage to electronic components.



ESD programs maintain an equal potential by maintaining continuous contact with ground, avoiding ESD damage. Cleaners, lotions, and coatings are an integral part of an ESD control program.



### Fast drying anti-static coating

Fast drying, anti-static coating eliminates static charge and reduces triboelectric generation from flexible surfaces. Ideal for plastics, fabrics, and carpet.

- All-purpose static control
- Non-flammable
- Non-ozone depleting
- For plastics, fabrics, and carpet
- Fast drying

## Product Packaging

1726-QT  
Zero Charge Anti-Stat Coating  
1 qt  
12 units/case



Chemical & Physical Properties	
Appearance	Clear, colorless liquid
Odor	Pleasant
Flash Point	none
VOC (EPA)	58.14 g/l
VOC (CARB)	
Boiling Point	100°C (212°F)
Density	0.978 at 25°C

### Chemical Composition

CHEMICAL NAME	CAS #
Ethylbis (hydroxyethyl) tallow alkyl, ethoxylated, Et sulfates	68071-95-4



Techspray - US office, P.O. Box 949,  
Amarillo, TX 79105-0949,  
Tel. 806-372-8523, Toll-free 800-858-4043  
Fax 806-372-8750, [tsales@techspray.com](mailto:tsales@techspray.com)



Ethanol	64-17-5
2-Propanol	67-63-0
Methanol	67-56-1

**Environmental Policy**

Techspray is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

**Resources**

Techspray products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray products in the United States, call the technical sales department at 800-858-4043, email [tsales@techspray.com](mailto:tsales@techspray.com) or visit our web site at: [www.techspray.com](http://www.techspray.com).

**North America**

Techspray  
P.O. Box 949  
Amarillo, TX 79105  
800-858-4043  
email: [tsales@techspray.com](mailto:tsales@techspray.com)

**Europe**

ITW Contamination Control BV  
Saffierlaan 5  
2132 VZ Hoofddorp  
The Netherlands  
+31 88 1307 400  
email: [info@itw-cc.com](mailto:info@itw-cc.com)

**Countries Outside US**

Call to locate a distributor in your country

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.

