



## MINISMDC110F-2 Product Details



**MINISMDC110F-2**

TE Internal Number: RF1406-000

Active

### PolySwitch Resettable Devices

Always EU RoHS/ELV Compliant (Statement of Compliance)

#### Product Highlights:

- Surface Mount Application
- Vmax = 8 V
- Imax = 100 A
- Family Name = miniSMD
- Surface Mount Construction

Documentation & Additional Information	
<p><b>Product Drawings:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Catalog Pages/Data Sheets:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">CP CATALOG 2011 - SURFACE-MOUNT</a> (PDF, English)</li> </ul> <p><b>Product Specifications:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">miniSMD110F</a> (PDF, English)</li> </ul> <p><b>Application Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Instruction Sheets:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>CAD Files:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul>	<p><b>Related Products:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Tooling</a></li> </ul>

Product Features (Please use the Product Drawing for all design activity)	
<p><b>Product Type Features:</b></p> <ul style="list-style-type: none"> <li>• Family Name = miniSMD</li> <li>• UL File Number = E74889</li> <li>• CSA File Number = CA78165</li> </ul> <p><b>Electrical Characteristics:</b></p> <ul style="list-style-type: none"> <li>• Vmax (V) = 8</li> <li>• Imax (A) = 100</li> <li>• IH (Room Temperature) (A) = 1.1</li> <li>• IT (Room Temperature) (A) = 2.20</li> <li>• Rmin (<math>\Omega</math>) = 0.04</li> <li>• R1 Max [Post Trip] (<math>\Omega</math>) = 0.21</li> </ul> <p><b>Termination Features:</b></p> <ul style="list-style-type: none"> <li>• Construction = Surface Mount</li> </ul> <p><b>Configuration Features:</b></p> <ul style="list-style-type: none"> <li>• Form Factor (inches) = 1812</li> <li>• Form Factor (mm) = 4532</li> </ul>	<p><b>Industry Standards:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">RoHS/ELV Compliance</a> = RoHS compliant, ELV compliant</li> <li>• <a href="#">Lead Free Solder Processes</a> = Reflow solder capable to 245°C, Reflow solder capable to 260°C</li> <li>• RoHS/ELV Compliance History = Always was RoHS compliant</li> <li>• TUV Certificate No. = R72111045</li> </ul> <p><b>Environmental:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Operating Temperature (Max.)</a> (<math>^{\circ}</math>C) = 85</li> </ul> <p><b>Operation/Application:</b></p> <ul style="list-style-type: none"> <li>• Application = Surface Mount</li> </ul> <p><b>Packaging Features:</b></p> <ul style="list-style-type: none"> <li>• Packaging Method = Tape &amp; Reel</li> </ul> <p><b>Other:</b></p> <ul style="list-style-type: none"> <li>• Brand = Raychem</li> </ul>