

1. INTRODUCTION

The guidelines listed in Table 1 are applicable to Appliance Tubing products.

| PRODUCT | DIMENSIONAL LIFE (Months) ² | STORAGE CONDITIONS ² |
|----------|---|------------------------------------|
| AP-2000 | 60 | 0°C to 35°C |
| AP2000 | 60 | 0°C to 35°C |
| ATUM | 60 | 0°C to 35°C |
| BRST | 144 | 0°C to 35°C |
| BSTS | 144 | 0°C to 35°C |
| BSTS-FR | 48 | 0°C to 35°C |
| CGAT | 60 | 0°C to 35°C |
| CGPT | 144 | 0°C to 35°C |
| CGPE-105 | 144 | 0°C to 35°C |
| CRN | 144 | 0°C to 35°C |
| DCPT | 144 | 0°C to 35°C |
| DSPL | 36 | 0°C to 35°C |
| DWP-125 | 60 | 0°C to 35°C |
| DWTC | 36 | 0°C to 30°C |
| DWFR | 60 | 0°C to 35°C |
| ES-CAPS | 36 | 0°C to 35°C |
| ES1000 | 36 | 0°C to 35°C |
| ES2000 | 36 | 0°C to 35°C |
| FL2500 | 36 | 0°C to 35°C |
| FLT | 36 | 0°C to 35°C |
| FP21 | 144 | 0°C to 35°C |
| GPO-135 | 144 | 0°C to 35°C |
| HF | 144 | 0°C to 35°C |
| HFT5000 | 144 | 0°C to 35°C |
| HRHF | 144 | 0°C to 35°C |
| HRHT | 36 | 0°C to 35°C |
| HRNF | 144 | 0°C to 35°C |
| HRSR | 144 | 0°C to 35°C |
| HT-200 | 144 | 0°C to 35°C |
| HTAT | 36 | 0°C to 35°C |
| LSTT | 144 | 0°C to 30°C |
| MIL-LT | 144 | 0°C to 35°C |
| NETM1000 | 144 | 0°C to 35°C |
| NETM2000 | 144 | 0°C to 35°C |

Table 1 (cont'd)

| PRODUCT | DIMENSIONAL LIFE (Months) ² | STORAGE CONDITIONS ² |
|---------------|---|------------------------------------|
| NYLON | 144 | 0°C to 35°C |
| PTCM | 36 | 0°C to 30°C |
| PD CAPS | 144 | 0°C to 35°C |
| QSAP-Cross | 36 | 0°C to 35°C |
| QSAP | 36 | 0°C to 35°C |
| QS1500 | 60 | 0°C to 35°C |
| QSZH | 36 | 0°C to 35°C |
| RAYFLEX | 144 | 0°C to 35°C |
| RAYRIM | 36 | 0°C to 35°C |
| RBK-85-kits | 36 | 0°C to 35°C |
| RBK-105-kits | 36 | 0°C to 35°C |
| RBK-ESS-CROSS | 36 | 0°C to 35°C |
| RBK-ESS-RING | 36 | 0°C to 35°C |
| RBK-ILS-125 | 36 | 0°C to 35°C |
| RBK-MTS | 36 | 0°C to 35°C |
| RBK-RTP-125 | 36 | 0°C to 35°C |
| RBK-VWS-125 | 36 | 0°C to 35°C |
| RHW | 60 | 0°C to 35°C |
| RMW | 60 | 0°C to 35°C |
| RNF-100 | 144 | 0°C to 35°C |
| RNF-150 | 144 | 0°C to 35°C |
| RNF-3000 | 144 | 0°C to 35°C |
| RP-4800 | 144 | 0°C to 35°C |
| RPPM | 36 | 0°C to 30°C |
| RPT-120 | 60 | 0°C to 35°C |
| RT-3 | 144 | 0°C to 35°C |
| RT-218 | 144 | 0°C to 35°C |
| RT-220 | 144 | 0°C to 35°C |
| RT-375 | 144 | 0°C to 35°C |
| RW-175 | 144 | 0°C to 35°C |
| RW-175-E | 144 | 0°C to 35°C |
| SAS S1017 | 36 | 0°C to 35°C |
| SAS S1030 | 60 | 0°C to 35°C |
| SAS S1048 | 36 | 0°C to 35°C |
| SAS S1124 | 60 | 0°C to 35°C |
| SCL | 144 | 0°C to 35°C |
| SCT | 36 | 0°C to 35°C |
| SST | 144 | 0°C to 35°C |

Table 1 (cont'd)

| PRODUCT | DIMENSIONAL LIFE (Months) ² | STORAGE CONDITIONS ² |
|-----------------|--|---|
| SST-FR | 36 | 0°C to 35°C |
| TAK-Caps | 36 | 0°C to 35°C |
| TAK-Sleeves | 36 | 0°C to 35°C |
| TAT-125 | 60 | 0°C to 35°C |
| TAT-Nylon | 144 | 0°C to 35°C |
| TC Caps | 144 | 0°C to 35°C |
| TFE/TFER | 144 | 0°C to 35°C |
| TPEM | 36 | 0°C to 35°C |
| TSAS | 36 | 0°C to 35°C |
| TUGA | 144 | 0°C to 35°C |
| URHT | 36 | 0°C to 35°C |
| VERSAFIT | 144 | 0°C to 35°C |
| VERSAFIT V2 | 144 | 0°C to 35°C |
| VERSAFIT V4 | 144 | 0°C to 35°C |
| VERSAFIT-3X | 144 | 0°C to 35°C |
| VERSAFLEX | 144 | 0°C to 35°C |
| VERSAFLEX-FR | 144 | 0°C to 35°C |
| VERSAFLEX-FR-UL | 144 | 0°C to 35°C |
| VFP21 | 144 | 0°C to 35°C |
| XFFR | 144 | 0°C to 35°C |
| ZH-100 | 144 | 0°C to 35°C No Exposure to Exhaust Gases |
| ZH2 | 144 | 0°C to 35°C |
| ZH4 | 144 | 0°C to 35°C |

Table 1 (end)

NOTES:

¹Shelf Life is based on standard size products. For over-expanded or special size products, please consult TE Connectivity.

²When stored properly in the original unopened packaging, out of direct sunlight and at normal room temperature (18°C to 35°C [65°F to 95°F]) unless otherwise noted. Storage conditions include storage during transportation.

The above are guidelines only based on 30 years of experience. TE Connectivity cannot provide any test data to validate the above.

While TE has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. In no event will TE be liable for any direct, indirect, incidental, special or consequential damages arising from or related to recipient's use of the information. It is the sole responsibility of recipient of this information to verify the results of this information using their engineering and product environment. Recipient assumes any and all risks associated with the use of the information.

2. REVISION SUMMARY

- Initial release of document.