



What can we help you find?



Email

Industries Products About TE Support Center My Account Resources

Home > Products > Protection Products > Product Feature Selector > Product Details

SO175-4-01 Product Details



S0175-4-01

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Shield Terminator
- Terminator Type = Solder Sleeve
- Fluid Resistance = Splash Protection
- Cable Temperature Rating = 175 °C
- Jacket Outer Diameter = 5.97 mm

View all Features

TE Internal Number: E64736-000













Quick Links-

📴 Share

- Check Pricing & Availability
- Search for Tooling
- Product Feature Selector
- ▶ Contact Us About This Product

Print

Documentation & Additional Information

Product Drawings:

SolderSleeve Shield Terminator, with Pre-installed B... (PDF, English)

Catalog Pages/Data Sheets:

None Available

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files:

• None Available

Additional Information:

Product Line Information

Related Products:

Tooling

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

• Product Type = Shield Terminator

Mechanical Attachment:

• Inside Diameter (mm [in]) = 5.95 [0.235]

Body Features:

- Terminator Type = Solder Sleeve
- <u>Jacket Outer Diameter (mm [in])</u> = 5.97 [0.235]

Housing Features:

- Shield O.D. (Min.) (mm [in]) = 3.30 [0.130]
- Preinstalled Lead = With
- Preinstalled Lead Wire Size (mm² [AWG]) = Braid Strap 640 [CMA 640]
- MIL or NAS Specification (MIL-S-83519) (NAS 1747) = No.
- Length (Max.) (mm [in]) = 19.10 [0.750]

Configuration Features:

- Temperature Indication System = With
- Temperature Indication System Type = Fusible Ring

Industry Standards:

List all Documents

- Government/Industry Qualification = No
- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Environmental:

- Fluid Resistance = Splash Protection
- Operating Temperature (Max.) (°C) = 175

Conditions for Usage:

Cable Temperature Rating (°C) = 175

Other:

Brand = Raychem

Corporate Information

Who We Are Investors News Room

Supplier Portal

Careers

Quick Links

Cross Reference

Check Distributor Inventory

Find Documents & Drawings

Product Compliance Support Center

Site Map

Customer Support

Email or Chat With Us Find a Phone Number Search Knowledge Base

Manage your Account

Keep Me Informed

Receive TE News, Events & Technology Updates

Enter your email address







