

10-ft. IEEE 1394b FireWire 800 Gold Hi-speed Cable (9pin/6pin)

MODEL NUMBER: F017-010



Highlights

- Connects Firewire 800 devices to legacy 1394a ports
- Meets FireWire 800 and 1394b Specifications
- Backward compatible to Original FireWire components

Applications

- Storage devices, Digital camcorders, Printers, Scanners, and other IEEE-1394b compatible devices

Package Includes

- 10ft IEEE-1394b FireWire 800 Gold Hi-Speed 9pin/6pin Cable

Description



Tripp Lite's IEEE-1394b, or FireWire 800 cables, are the latest in FireWire technology, with data transfer speeds up to 800Mbps, twice the speed of original FireWire. The 9-pin to 6-pin FireWire 800 - FireWire cable (also known as a "bilingual" cable) will connect a 6-pin FireWire (1394a) device to a 9-pin FireWire 800 (1394b) port on a computer, or it will connect the 6-pin FireWire port on a computer to a 9-pin FireWire 800 device (FireWire 800 devices can achieve FireWire 800 speeds only when connected to a FireWire 800 port). These cables are 100% compatible with Apple FireWire, Sony iLink, and all other IEEE-1394b peripherals.

Features

- Data transfer rates to 800Mbps
- Hot Pluggable - supports Plug-n-Play operation
- Premium triple-shielded cable with molded, Gold connectors
- Backward compatible with FireWire systems and devices
- Compatible with PC, Mac, SUN, and other IEEE-1394b equipped systems

Specifications

OVERVIEW	
Intended Application	Connecting Peripherals
Cable Type	FIREWIRE
Model Type	1394b (800)
INPUT	
Cable Length (ft.)	10

Cable Length (m)	3.05
UPC ASSIGNMENT	
Unit Carton UPC#	037332124593
PHYSICAL	
Color	Black
Style	FireWire
CONNECTIONS	
Connector A	 9 PIN (MALE)
Connector B	 6 PIN (MALE)
Number of Connectors	2
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.