

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Fiber Optic Mode Conditioning Patch Cable (ST/LC), 3M (10 ft.)

MODEL NUMBER: N422-03M



Description

Tripp Lites Mode Conditioning Cables are designed for use in Gigabit Ethernet 1000BASE-LX applications. They are fully compliant with IEEE 802.3z application standards. Mode Conditioning Cables are needed in applications where new high-speed Gigabit 1000BASE-LX routers and switches are being deployed into existing multimode plants. The need for this patch cord is due to the single-mode launch nature of the -LX or long-wave (1300 nm) transceiver modules used for Gigabit Ethernet. Launching a single-mode laser into the center of a multimode fiber can cause multiple signals to be generated that confuses the receiver at the other end of the fiber. These multiple signals, caused by Differential Mode Delay (DMD) effects, severely limit the cable distance lengths for operating Gigabit Ethernet. A mode conditioning patch cord eliminates these multiple signals by allowing the single-mode launch to be offset away from the center of a multimode fiber.

Features

- Use Singlemode Transceivers on Multimode Fiber Backbones
- 62.5/125 and 8.3/125
- Offsets the Singlemode Laser launch from the center of a Multimode fiber
- Available in a variety of connector combinations

Specifications

OVERVIEW	
UPC Code	037332129918
Clad Diameter	125 micron; 125 micorn
Core Diameter	62.5 micron; 8.3 micron
Number of Fibers	2

Highlights

- 3 Meter LC/ST Mode
 Conditioning Cable
- 62.5/125 and 8.3/125
- Run 1000Base-LX Gigabit
 Ethernet over MMF by offsetting signal loss
- IEEE 802.3z Gigabit Ethernet
 Compliant

Package Includes

 3 Meter LC/ST Mode Conditioning Cable



INPUT		
Cable Length (ft.)	9.8	
Cable Length (m)	3	
Cable Length (in.)	118.1	
PHYSICAL		
Color	Orange; Yellow	
Shipping Dimensions (hwd / cm)	22.86 x 17.78 x 1.27	
Shipping Dimensions (hwd / in.)	9.00 x 7.00 x 0.50	
Shipping Weight (kg)	0.05	
Shipping Weight (lbs.)	0.12	
CONNECTIONS		
Side A - Connector 1	LC DUPLEX (MALE)	
Side B - Connector 1	ST DUPLEX (MALE)	
FEATURES & SPECIFICATIONS		
Technology	Mode Conditioning	
SPECIAL FEATURES		
Push/Pull Tabs	No	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies