

3M (10-ft.) Fiber Optic Mode Conditioning Patch Cable (SC/SC)

MODEL NUMBER: N426-03M



Highlights

- 3 Meter SC/SC Mode Conditioning Cable
- 62.5/125 and 8.3/125
- Run 1000Base-LX Gigabit
 Ethernet over MMF by offsetting signal loss
- IEEE 802.3z Gigabit Ethernet Compliant

Applications

 Use when connecting a LX type fiber transceiver (Singlemode light) to a Multimode backbone

Package Includes

 3 Meter SC/SC Mode Conditioning Cable

Description

Tripp Lites Mode Conditioning Cables are designed for use in Gigabit Ethernet 1000BASE-LX applications. They are fully compliant with IEEE 802.3z application standards. Mode Conditioning Cables are needed in applications where new high-speed Gigabit 1000BASE-LX routers and switches are being deployed into existing multimode plants. The need for this patch cord is due to the single-mode launch nature of the -LX or long-wave (1300 nm) transceiver modules used for Gigabit Ethernet. Launching a single-mode laser into the center of a multimode fiber can cause multiple signals to be generated that confuses the receiver at the other end of the fiber. These multiple signals, caused by Differential Mode Delay (DMD) effects, severely limit the cable distance lengths for operating Gigabit Ethernet. A mode conditioning patch cord eliminates these multiple signals by allowing the single-mode launch to be offset away from the center of a multimode fiber.

Features

- Use Singlemode Transceivers on Multimode Fiber Backbones
- 62.5/125 and 8.3/125
- Offsets the Singlemode Laser launch from the center of a Multimode fiber
- Available in a variety of connector combinations

Specifications

OVERVIEW		
Intended Application	Computer Networking (Fiber)	
Cable Type	MODE CONDITIONING FIBER OPTIC	
INPUT		
Cable Length (m)	3	





UPC ASSIGNMENT			
Unit Carton UPC#	037332127297		
PHYSICAL			
Color	Orange & Yellow		
Style	Fiber Optic		
CONNECTIONS			
Connector A	SC SC		
Connector B	SC SC		
Number of Connectors	4		
WARRANTY			
Product Warranty Period (Worldwide)	Lifetime limited warranty		

Related Items

Optional Products

Model Number	Description	Qty.
N422-01M	1M (3-ft.) Fiber Optic Mode Conditioning Patch Cable (ST/LC)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at: http://www.tripplite.com/sku/N426-03M.

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.